



PRINCE EDWARD ISLAND
ÎLE-DU-PRINCE-ÉDOUARD

PLANNING ACT PROVINCE-WIDE MINIMUM DEVELOPMENT STANDARDS REGULATIONS

PLEASE NOTE

This document, prepared by the *Legislative Counsel Office*, is an office consolidation of this regulation, current to November 19, 2011. It is intended for information and reference purposes only.

This document is *not* the official version of these regulations. The regulations and the amendments printed in the *Royal Gazette* should be consulted on the Prince Edward Island Government web site to determine the authoritative text of these regulations.

For more information concerning the history of these regulations, please see the *Table of Regulations* on the Prince Edward Island Government web site (www.princeedwardisland.ca).

If you find any errors or omissions in this consolidation, please contact:

Legislative Counsel Office

Tel: (902) 368-4292

Email: legislation@gov.pe.ca



PLANNING ACT
Chapter P-8

**PROVINCE-WIDE MINIMUM DEVELOPMENT STANDARDS
REGULATIONS**

Pursuant to clause 7(1)(c) of the *Planning Act* R.S.P.E.I. 1988, Cap. P-8, Council made the following regulations:

1. “authority having jurisdiction”, defined

- (1) In these regulations “**authority having jurisdiction**” means the Minister responsible for the *Planning Act* R.S.P.E.I. 1988, Cap. P-8, or in the case of a municipality with an official plan and bylaws, the municipal council.

Idem, existing definitions

- (2) Words and expressions defined in section 1 of the *Planning Act* Subdivision and Development Regulations have the same meaning when used in these regulations. (EC703/95; 552/11)

2. Application

These regulations apply to all areas of the province. (EC703/95)

3. Lot size

Revoked by EC41/96.

4. Residential

- (1) No approval or permit shall be granted for the subdivision of a lot for residential use unless the lot conforms with the minimum lot size standards set out in Table 1.

Location

- (2) The area encompassed by the required minimum circle diameter as set out in Table 1 and Table 2 shall be located on the lot such that it will accommodate an on-site sewage disposal system.

Reduced size

- (3) Notwithstanding the minimum lot size standards set out in Table 1 and Table 2, for infilling purposes, a lot may be reduced to a minimum of 10,000 sq. ft. / 929 sq. m. provided that

- (a) it is serviced by an on-site water supply system and a central sewerage system; and
- (b) only one additional lot from the existing parcel is created by any proposed subdivision.

Reduced circle requirement

- (4) Notwithstanding the minimum circle diameter requirements set out in column (f) of Table 1 and column (e) of Table 2, a lot that does not meet those requirements may be subdivided from a lot or parcel that existed prior to June 12, 1993 where
 - (a) the lot is intended for either single unit residential use or non-residential use, and will be serviced by on-site water and sewerage disposal systems;
 - (b) the lot meets Category I standards in accordance with clause 5(a) and the minimum lot area requirements set out in column (e) of Table 1 and column (d) of Table 2 respectively;
 - (c) a circle with a minimum diameter of 125 ft./38.1 m. will fit within the boundaries of the lot; and
 - (d) there is no practical alternative to increasing the size of the property to permit compliance with the circle diameter requirement. (*EC703/95; 41/96; 694/00; 552/11*)

5. Non-residential

- (1) No approval or permit shall be issued to subdivide a lot for non-residential use unless in conformity with the minimum lot size standards set out in Table 2.

Exception

- (2) Notwithstanding subsection (1),
 - (a) where a lot is intended for any non-residential use where water and sewage services are not required for the proposed development, the Minister may approve an exemption from the requirement of subsection (1);
 - (b) where an approval or permit has been granted by an authority having jurisdiction pursuant to subsection (1), a subsequent approval or permit requiring or proposing a sewerage system shall only be granted in accordance with the standards set out in Table 2. (*EC703/95; 41/96; 552/11*)

6. Categories of lots

Every lot on a plan of subdivision shall be categorized in accordance with the following site suitability standards:

- (a) Category I, where
 - (i) the depth of permeable natural soil is 2 ft. (0.61 m.) or greater,
 - (ii) the depth to bedrock is 4 ft. (1.22 m.) or greater, and
 - (iii) the depth to the maximum groundwater elevation is 4 ft. (1.22 m.) or greater;
- (b) Category II, where
 - (i) the depth of permeable natural soil is greater than 1 ft. (0.3 m.), but less than 2 ft. (0.61 m.),
 - (ii) the depth to bedrock is 4 ft. (1.22 m.) or greater, and
 - (iii) the depth to the maximum groundwater elevation is 4 ft. (1.22 m.) or greater;
- (c) Category III, where
 - (i) the depth of permeable natural soil is 1 ft. (0.3 m.) or greater,



- (ii) the depth to bedrock is 2 ft. (0.61 m.) or greater, but less than 4 ft. (1.22 m.),
or
- (iii) the depth to the maximum groundwater elevation is 2 ft. (0.61 m.) or greater,
but less than 4 ft. (1.22 m.);
- (d) Category IV, where
 - (i) the lot has a depth of permeable natural soil of less than 1 ft. (0.3 m.),
 - (ii) the depth to bedrock is greater than 1 ft. (0.3 m.), and
 - (iii) the depth of the maximum groundwater elevation is greater than 2 ft. (0.61 m.);
- (e) Category V, where
 - (i) the depth to bedrock is less than 1 ft. (0.3 m.), and
 - (ii) the depth to the maximum ground water elevation is greater than 2 ft. (0.61 m.). (*EC703/95; 694/00; 552/11*)

7. Upgrade

Revoked by (*EC694/00*).

8. Application

The minimum lot size standards set in Tables 1 and 2 do not apply to subdivisions approved prior to October 14, 1995. (*EC703/95; 552/11*)

9. Minor variance

- (1) The authority having jurisdiction may, for special cause, authorize such minor variance from the provisions of these regulations as, in its opinion, is desirable and not inconsistent with the general intent and purpose of these regulations.

Variance, public utility use

- (2) Notwithstanding any other provisions of these regulations, where a lot is designed for use by a public or a private utility, the authority having jurisdiction may authorize a variance from the provisions of these regulations as, in its opinion, is desirable. (*EC703/95; 552/11*)

MINIMUM HIGHWAY ACCESS

10. Minimum highway access standards

- (1) The *Roads Act* Highway Access Regulations shall constitute the Minimum Highway Access Standards.

Entrance way permit

- (2) An authority having jurisdiction shall not grant an approval or issue a permit for development unless an entrance way permit has been obtained for the applicable lot or development when so required. (*EC703/95; 2/96; 552/11*)

TABLE 1
MINIMUM LOT SIZE STANDARDS:
RESIDENTIAL LOTS

(a) Servicing	(b) Lot Category	(c) Minimum Lot Frontage	(d) Number of Dwelling Units	(e) Minimum Lot Area sq. ft. / sq. m.	(f) Minimum Circle Diameter to be Contained Within the Boundaries of the Lot - feet / metres
on-site water supply and on-site sewage disposal system	I	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	1 2 3 4 more than 4 4	25,000 sq. ft. / 2,322.5 sq. m. 30,000 sq. ft. / 2,787 sq. m. 35,000 sq. ft. / 3,251.5 sq. m. 40,000 sq. ft. / 3,717 sq. m. 40,000 sq. ft. / 3,717 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	150 ft. / 45.7 m. 160 ft. / 48.8 m. 175 ft. / 53.3 m. 200 ft. / 61 m. 200 ft. / 61 m.
on-site water supply and on-site sewage disposal system	II	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	1 2 3 4 more than 4 4	35,000 sq. ft. / 3,251.5 sq. m. 40,000 sq. ft. / 3,717 sq. m. 45,000 sq. ft. / 4,180.5 sq. m. 50,000 sq. ft. / 4,645 sq. m. 50,000 sq. ft. / 4,645 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	175 ft. / 53.3 m. 200 ft. / 61 m. 225 ft. / 68.6 m. 250 ft. / 76.2 m. 250 ft. / 76.2 m.
on-site water supply and on-site sewage disposal system	III	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	1 2 3 4 more than 4 4	51,000 sq. ft. / 4,738 sq. m. 56,000 sq. ft. / 5,202 sq. m. 61,000 sq. ft. / 5,667 sq. m. 66,000 sq. ft. / 6,131 sq. m. 66,000 sq. ft. / 6,131 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	225 ft. / 68.6 m. 250 ft. / 76.2 m. 275 ft. / 83.8 m. 300 ft. / 91.4 m. 300 ft. / 91.4 m.
on-site water supply and on-site sewage disposal system	IV	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	1 2 3 4 more than 4 4	75,000 sq.ft. / 6,975 sq.m. 80,000 sq.ft. / 7,440 sq.m. 85,000 sq.ft. / 7,905 sq.m. 90,000 sq.ft. / 8,370 sq.m. 90,000 sq.ft. / 8,370 sq.m., plus 1,500 sq.ft. / 457 sq.m. for each additional unit	300 ft. / 91.4 m.
on-site water supply and on-site sewage disposal system	V	N/A	N/A	not developable	N/A

TABLE 1

(a) Servicing	(b) Lot Category	(c) Minimum Lot Frontage	(d) Number of Dwelling Units	(e) Minimum Lot Area sq. ft. / sq. m.	(f) Minimum Circle Diameter to be Contained Within the Boundaries of the Lot - feet / metres
central water supply and on-site sewage disposal system	I	50 feet / 15.25 metres	1 2 3 4 more than 4	20,000 sq. ft. / 1,858 sq. m. 25,000 sq. ft. / 2,322.5 sq. m. 30,000 sq. ft. / 2,787 sq. m. 35,000 sq. ft. / 3,251.5 sq. m. 35,000 sq. ft. / 3,251 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	125 ft. / 38.1 m. 150 ft. / 45.7 m. 160 ft. / 48.8 m. 175 ft. / 53.3 m. 175 ft. / 53.3 m.
central water supply and on-site sewage disposal system	II	50 feet / 15.25 metres	1 2 3 4 more than 4	25,000 sq. ft. / 2,322.5 sq. m. 30,000 sq. ft. / 2,787 sq. m. 35,000 sq. ft. / 3,251.5 sq. m. 40,000 sq. ft. / 3,717 sq. m. 40,000 sq. ft. / 3,717 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	150 ft. / 45.7 m. 160 ft. / 48.8 m. 175 ft. / 53.3 m. 200 ft. / 61 m. 200 ft. / 61 m.
central water supply and on-site sewage disposal system	III	50 feet / 15.25 metres	1 2 3 4 more than 4	40,000 sq. ft. / 3,717 sq. m. 45,000 sq. ft. / 4,180.5 sq. m. 50,000 sq. ft. / 4,645 sq. m. 55,000 sq. ft. / 5,110 sq. m. 55,000 sq. ft. / 5,110 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	200 ft. / 61 m. 225 ft. / 68.6 m. 250 ft. / 76.2 m. 275 ft. / 83.8 m. 275 ft. / 83.8 m.
central water supply and on-site sewage disposal system	IV	50 feet / 15.25 metres	1 2 3 4 more than 4	60,000 sq. ft. / 5,580 sq. m. 65,000 sq. ft. / 6,450.5 sq. m. 70,000 sq. ft. / 6,510 sq. m. 75,000 sq. ft. / 6,975 sq. m. 75,000 sq. ft. / 6,975 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	275 ft. / 83.8 m.
central water supply and on-site sewage disposal system	V	N/A	N/A	not developable	N/A
on-site water supply and central waste treatment system	I or II	50 feet / 15.25 metres	1 2 3 4 more than 4	15,000 sq. ft. / 1,393.5 sq. m. 20,000 sq. ft. / 1,858 sq. m. 25,000 sq. ft. / 2,322.5 sq. m. 30,000 sq. ft. / 2,787 sq. m. 30,000 sq. ft. / 2,787 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	100 ft. / 30.5 m. 125 ft. / 38.1 m. 150 ft. / 45.7 m. 160 ft. / 48.8 m. 160 ft. / 48.8 m.
on-site water supply and central waste treatment system	III	50 feet / 15.25 metres	1 2 3 4 more than 4	20,000 sq. ft. / 1,858 sq. m. 25,000 sq. ft. / 2,322.5 sq. m. 30,000 sq. ft. / 2,787 sq. m. 35,000 sq. ft. / 3,251.5 sq. m. 35,000 sq. ft. / 3,251.5 sq. m., plus 1,500 sq. ft. / 457 sq. m. for each additional unit	125 ft. / 38.1 m. 150 ft. / 45.7 m. 160 ft. / 48.8 m. 175 ft. / 53.3 m. 175 ft. / 53.3 m.



(a) Servicing	(b) Lot Category	(c) Minimum Lot Frontage	(d) Number of Dwelling Units	(e) Minimum Lot Area sq. ft. / sq. m.	(f) Minimum Circle Diameter to be Contained Within the Boundaries of the Lot - feet / metres
central water supply and waste treatment systems	I, II, or III	n/a	any number	as determined by the Minister	as determined by the Minister

TABLE 2

TABLE 2
MINIMUM LOT SIZE STANDARDS:
NON-RESIDENTIAL LOTS

(a) Servicing	(b) Lot Category	(c) Minimum Lot Frontage	(d) Minimum Lot Area	(e) Minimum Circle Diameter to be Contained Within the Boundaries of the Lot - feet/metres
on-site water supply and on-site sewage disposal system	I	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	25,000 sq. ft. / 2,322.5 sq. m.	150 ft. / 45.7 m.
on-site water supply and on-site sewage disposal system	II	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	35,000 sq. ft. / 3,251.5 sq. m.	175 ft. / 53.3 m.
on-site water supply and on-site sewage disposal system	III	100 feet / 30.5 metres (or 50 feet / 15.25 metres, where the frontage is on the interior curve of a street)	51,000 sq. ft. / 4,738 sq. m.	225 ft. / 68.6 m.
central water supply and on-site sewage disposal system	I	50 feet / 15.25 metres	20,000 sq. ft. / 1,858 sq. m.	125 ft. / 38.1 m.
central water supply and on-site sewage disposal system	II	50 feet / 15.25 metres	25,000 sq. ft. / 2,322.5 sq. m.	150 ft. / 45.7 m.
central water supply and on-site sewage disposal system	III	50 feet / 15.25 metres	35,000 sq. ft. / 3,251.5 sq. m.	175 ft. / 53.3 m.
on-site water supply and central waste treatment system	I, II or III	50 feet / 15.25 metres	15,000 sq. ft. / 1,393.5 sq. m.	100 ft. / 30.5 m.
central water supply and waste treatment systems	I, II or III	n/a	as determined by the Minister	as determined by the Minister

(EC542/87; 703/95; 694/00; 552/11)

